

**ACR Series**

**ACR (AIR CLEANER RETROFIT)  
ELECTRONIC UPGRADE**

Upgrades ACB and ACM Series Air Cleaners to a SST Series Electronic Air Cleaner

**FEATURES**

- -100 models no air switch, -150 models include air switch and 6' power cord.
- Easy to install.
- Snap-on power door.
- Twin 5" collecting cells.
- Upgrades ACB and ACM Series air cleaners to a SST Series Electronic Air Cleaner.

**SPECIFICATIONS**

Dimensions . . . . . Fits ACB & ACM Series compartments page 46


**PARTS AND ACCESSORIES**

- Replacement charcoal filters: Refer to page 198

Model Number	CFM	Recommended CFM	A/C Tonnage	BTU Input Range	Power Requirements	Shipping Weight
ACR1000-101*	1000	600-1200	up to 3.0	up to 120,000	120 VAC, .3A, 50/60 Hz	42 lbs.
ACR1000-151*	1000	600-1200	up to 3.0	up to 120,000	120 VAC, .3A, 50/60 Hz	42 lbs.
ACR1400-101*	1400	1000-1600	up to 4.0	up to 160,000	120 VAC, .3A, 50/60 Hz	46 lbs.
ACR1400-151*	1400	1000-1600	up to 4.0	up to 160,000	120 VAC, .3A, 50/60 Hz	46 lbs.
ACR1600-101*	1600	1200-1800	up to 4.5	up to 180,000	120 VAC, .3A, 50/60 Hz	46 lbs.
ACR1600-151*	1600	1200-1800	up to 4.5	up to 180,000	120 VAC, .3A, 50/60 Hz	46 lbs.
ACR2000-101*	2000	1600-2200	up to 5.5	up to 220,000	120 VAC, .3A, 50/60 Hz	48 lbs.
ACR2000-151*	2000	1600-2200	up to 5.5	up to 220,000	120 VAC, .3A, 50/60 Hz	48 lbs.

\*-100 Models (No Air Switch)

\*-150 Models (With Air Switch and 6' Electrical Cord)



**TTW1000**

**TTW (THRU-THE-WALL) SERIES  
ELECTRONIC AIR CLEANER**

Thru-The-Wall Electronic Air Cleaners for Closet, Ceiling or Attic Installations

**FEATURES**

- Cell removes easily for cleaning.
- Operating indicator light.
- Built-in air flow monitor switch.
- ON/OFF switch.
- Pre-filter.

**SPECIFICATIONS**

Agency . . . . . U.L. listed and C.S.A. certified

**PARTS AND ACCESSORIES** See page 199 for parts and accessories



**TECHNICAL HELP**

- Sizing . . . . . See page 196
- Parts view . . . . . See page 199
- Electronic Air Cleaner Parts Reference Guide . . . . . See page 211-229

Model Number	CFM	Size	Cabinet Dimensions	Recommended CFM	A/C Tonnage	BTU Input Range	Power Requirements	Shipping Weight
TTW1000	1000	19" x 26"	17.0"H x 23.3"W x 6.0"D	800 - 1000	up to 2.5	up to 100,000	120 VAC, .3A, 60Hz	40 lbs.
TTW1400	1400	26" x 26"	23.9"H x 23.3"W x 6.0"D	1000 - 1400	up to 3.5	up to 140,000	120 VAC, .3A, 60Hz	54 lbs.
TTW2000	2000	31" x 26"	28.9"H x 23.3"W x 6.0"D	1400 - 2000	up to 5.0	up to 200,000	120 VAC, .3A, 60Hz	68 lbs.